



3-Port HDMI Switcher 4K - Black



P/N: Switcher3P

Congratulations for owning a gofanco product. Our products aim to meet all your connectivity needs wherever you go. Have fun with our products!

Please read this manual carefully before first use.

If you need more information about our products, please visit www.gofanco.com.

For technical support, please email us at support@gofanco.com.

For drivers/manuals download, please go to <http://www.gofanco.com/download>.

Introduction

gofanco 3-Port HDMI Switcher 4K - Black (part# Switcher3P) allows any of the 3 HDMI sources to be displayed on one HDMI display and supports ultra-high resolution up to 4K.

Specifications

Spec.	HDMI v1.4
Compliance	HDCP 1.4, 36-bit deep Color, 3D
Video bandwidth	10.2Gbps
Video support	480p, 720p, 1080i, 1080p@60Hz, 4Kx2K (3840x2160 @60Hz)
Audio support	Dolby-trueHD, DTS-HD master audio 7.1-channel
Connectors	Input: HDMI x 3 Output: HDMI x 1
Transmission distance (4Kx2K @60Hz)	Input: 5m (Max.) for HDMI standard cable_26AWG Output: 5m (Max.) for HDMI standard cable_26AWG
Power cable	DC 5V / 0.5A
Dimensions	7.48" (W) x 2.34" (H) x 3.42" (D)
Weight	0.13lbs

Package Contents

- 3- Port HDMI Switcher 4K - Black
- Power cable
- IR remote control
- IR Receiver Extension cable
- User's guide

Layout



Figure 1: 3-Port HDMI Switcher 4K - Black

- **Input LEDs:** On when input signals are detected
- **Switch:** Select input source 1, 2, or 3
- **HDMI output:** Connects to an HDMI display or TV
- **Power plug:** Connects to the included power cable
- **IR port:** Plug IR receiver extension cable here



Figure 2: 3-Port HDMI Switcher 4K - Black

- **HDMI inputs:** Connect to HDMI source devices

IR Remote Control



Figure 3: IR Remote Control

- **Input Select Button:** Select input source 1, 2 or 3
- **Next:** Select the next input source



Figure 4: IR Receiver Extension cable

Hardware Installation

1. Power off all source devices and displays.
2. Connect up to 3 HDMI source devices to the switcher's HDMI input ports using HDMI cables (cables not included).
3. Connect your HDMI display to the switcher's HDMI Output with an HDMI cable (cable not included).
4. Connect the included power cable to the switcher's power plug and plug it into one of your systems' USB port.
Note: This power connection is OPTIONAL but recommended for a more stable performance.
5. Power on all of the connected devices.
6. The switcher is now ready for use.

Blank page



Thank you for choosing gofanco